

NX-3200/3300

VHF/UHF MULTI-PROTOCOL DIGITAL & ANALOG PORTABLE RADIOS

This versatile handheld radio supports both NXDN® and DMR digital protocols as well as mixed digital & FM analog operation, enabling it to serve with distinction in a wide range of enterprise and operation-critical applications. Compact yet designed with durability in mind, it's packed with convenient features like Bluetooth® for hands-free operation and built-in GPS. Three different models with 14-pin Universal connector are available: Full Keypad model with LCD, Standard Keypad model with LCD and a large 4-way D-pad, and the Basic Model without LCD or keypad. Additionally, for expansion capability a software license certification system facilitates extensive customization.

FEATURES

- Multi-protocol digital radio: Designed to operate under NXDN® or DMR digital, and FM analog protocols
- NXDN Conventional and Type-C & Gen2 Trunking
- DMR Tier II & Site Roaming
- Mixed Digital & FM Analog Operation allows gradual migration at your own pace
- 4-Line Basic Frame (2-Line Main/Sub-LCD, icon & key guide) / 14 Characters
- 5-Line Text Message Frame (3 Lines of Text, icon & key guide)
- 7-color Light Bar Indicator on the top panel
- 4-way Directional-pad (D-pad) for intuitive control and operation
- Built-in GPS Receiver/Antenna for effective fleet management
- Built-in Bluetooth for hands-free operation – Applicable Bluetooth profiles: HSP (Headset Profile provided) and SPP (Serial Port Profile available as an option)
- Renowned KENWOOD Audio Quality achieved with Active Noise Reduction (ANR) that utilizes built-in DSP
- Optional DES and AES Encryption
- Built-in Motion Sensor (Man-down, Stationary and Motion Detection)
- IP54/55/67 and MIL-STD-810 C/D/E/F/G
- 1 Watt Audio Output Power
- UHF: 120 MHz capability
- Available models: Full Keypad (w/ LCD and full keypad), Standard Keypad (w/ LCD and 4-way large D-pad/4 key), and Basic (w/o LCD and keypad)
- 512 CH/128 Zones (64 CH/4 Zones for Basic model)
- Maximum of 1,000 CH/Radio with option
- CSA Intrinsically Safe Class I, II, III, Division 1, Groups A, B, C, D, E, F, G

- Paging Call
- Emergency Call
- Status/Text Message
- Remote Stun/Kill/Check

DIGITAL – NXDN® MODE

- NXDN Type-C & Gen2 Trunked
- NXDN Conventional
- 6.25 & 12.5 kHz Channels
- All Group Call
- Over-the-Air Alias (OAA)
- Over-the-Air Programming (OTAP)

DIGITAL – DMR MODE

- Complies with ETSI DMR Tier II standards
- Two-slot TDMA in 12.5 kHz channels
- Call Interruption
- Dual-slot Direct Mode
- Optional ARC4 Encryption
- Energy Efficient
- Over-the-Air Alias (OAA)

ANALOG - FM MODE

- Conventional & LTR Trunking
- FleetSync/II: PTT ID ANI / Caller ID Display, Selective Group Call, Emergency Status / Text Messages
- MDC-1200: PTT ID ANI / Caller ID Display, Emergency, Radio Check / Inhibit
- QT / DQT, 2-Tone
- Built-in Voice Inversion Scrambler



Full Keypad Model
Standard & Basic Models



7-color Light Bar Indicator

14-pin Universal Connector offers reliable connectivity even in harsh environment with a wide-range of accessories.



Multi-Protocol

Unsurpassed interoperability for Public Safety and Enterprise radio users with the freedom to migrate at your own pace.



Gen2

Scalable server-based system architecture for management of NEXEDGE wide area digital communications systems.


























Klarity

The ultimate level of sound clarity technology combining Optimization, advanced Sound Analysis and Active Noise Reduction.

Accessories

NX-3200/3300 Portable Radios

■ KNB-55L/57L/78L Li-ion Battery Pack (7.4V/1480mAh, 7.4V/2000mAh, 7.4V/2860mAh) 	■ KSC-256K Multiple Charger (6-pocket) 	■ KRA-23 UHF Low Profile Helical Antenna 	■ KEP-1 Earphone (3.5mm) 	■ KBH-11 Belt Clip (2.5") 
■ KNB-79LC CSA IS Li-ion Battery Pack (7.4V/2860mAh) 	■ KMB-30 Mounting Bracket (for KSC-256) 	■ KRA-29P Broadband UHF Antenna 	■ KMC-41D Speaker Microphone (IP54/55) 	■ KPG-180P OTAP Manager 
■ KNB-56N Ni-MH Battery Pack (7.2 V/1400 mAh) 	■ KVC-4 Vehicular Charger 	■ KRA-25 High Gain Whip Antenna 	■ KMC-42WD Speaker Microphone (IP67) 	■ KLH-208P Heavy Duty Leather Case for use with KNB-57L/55L/56N/KPB-5 Batteries 
■ KBP-5 Battery Case (6 AA) 	■ KRA-22 VHF Low Profile Helical Antenna 	■ KRA-26 VHF Helical Antenna 	■ KMC-54WD Speaker Microphone (with dual-sided 2-mic for superior ANR, IP67) 	■ KLH-212P Heavy Duty Leather Case For use with KNB-78L/79LC Batteries 
■ KSC-25LSK/25SK Rapid Charger (Li-ion Only/Tri-Chem) 	■ KRA-27 UHF Whip Antenna 	■ KRA-28 Broadband VHF Whip Antenna 		

All accessories may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories.

Specifications

	NX-3200	NX-3300
GENERAL		
Frequency Range	136-174 MHz	400-520 MHz
Max. Channels Per Radio	Up to 1000 CH with option	
Number of Channels	512 (64 for no LCD models)	
Number of Zones	128 (4 for no LCD models)	
Channel Spacing		
Analog	12.5/15/25/30 kHz	12.5/25 kHz
Digital	6.25 kHz/12.5 kHz	
Power Supply	7.5V DC ± 20%	
Battery Life 5-5-90	(FDMA / TDMA)	
KNB-55L (1,480 mAh)	Approx. 8 hours / Approx. 9.5 hours	
KNB-56N (1,400 mAh)	Approx. 8 hours / Approx. 9 hours	
KNB-57L (2,000 mAh)	Approx. 11 hours / Approx. 13.5 hours	
Operating Temperature	-22°F to +140°F (-30°C to +60°C)	
Frequency Stability	±2.0 ppm	±1.0 ppm
Dimensions	(W x H x D) Projections Not Included	
Radio Only	2.20 x 4.71 x 1.43 in (56 x 119.6 x 36.4 mm)	
KNB-55L (1,480 mAh)	2.20 x 4.71 x 1.43 in (56 x 119.6 x 36.4 mm)	
KNB-56N (1,400 mAh)	2.20 x 4.71 x 1.68 in (56 x 119.6 x 42.7 mm)	
KNB-57L (2,000 mAh)	2.20 x 4.71 x 1.53 in (56 x 119.6 x 39 mm)	
Weight Radio Only	7.8 oz (220 g)	
KNB-55L (1,480 mAh)	11.1 oz (315 g)	
KNB-56N (1,400 mAh)	14.5 oz (410 g)	
KNB-57L (2,000 mAh)	12.0 oz (340 g)	
IC Certification	282F-479000	282F-479100

	NX-3200	NX-3300
RECEIVER		
Sensitivity		
NXDN® 6.25 kHz Digital (3% BER)	0.20 µV	
NXDN® 12.5 kHz Digital (3% BER)	0.25 µV	
DMR 12.5 KHz Digital (5% BER)	0.30 µV	
DMR 12.5 KHz Digital (1% BER)	0.45 µV	
Analog (12dB SINAD)	0.25 µV	
Selectivity		
Analog @ 12.5 kHz	65 dB	
Analog @ 25 kHz	72 dB	
Intermodulation	70 dB	
Spurious Rejection	70 dB	
Audio Distortion	3%	
Audio Output Power	500 mW/8Ω (3% Distortion) / 1,000 mW/8Ω (5% Distortion)	
TRANSMITTER		
RF Power Output (High / Mid / Low)	5 W / 4 W / 1 W	
Spurious Emission	70 dB	
FM Hum & Noise		
Analog @ 12.5 kHz	40 dB	
Analog @ 25kHz	45 dB	
Audio Distortion	Less than 3%	
Digital Protocol	ETSI TS 102 361-1, -2, -3	
Emission Designator	16K0F3E, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 7K60FXD, 7K60FXE, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D	

Analog measurements made per TIA603. Specifications are measured according to applicable standards. Specifications shown are typical and subject to change without notice, due to advancements in technology. CSA Intrinsically Safe Class I, II, III, Division 1, Groups A, B, C, D, E, F, G

The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. NXDN® is a registered trademark of JVCKENWOOD Corporation and Icom Inc. NEXEDGE® & FleetSync® are a registered trademarks of JVCKENWOOD Corporation. All other trademarks are the property of their respective holders.

MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV
International Protection Standard					
Dust & Water Protection*	IP67				

KENWOOD

JVCKENWOOD Canada Inc.
Canadian Headquarters and Distribution
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8
www.kenwood.com/ca



ISO9001 Registered
JVCKENWOOD Corporation
ADS#13918 Printed in USA